

Altura 1100

Efficiency made simple

By Cuata, Granda Partners LLC

Full servo Window Patcher (CE Certification)



Altura 1100

Main features at a glance:

High Performance

1. High-Speed Efficiency: Up to 60,000 blanks/hr in double stream.
2. Independent servo-controlled feed for each lane.
3. Exceptional precision, ± 1.0 mm film accuracy thanks to our full-servo system and proprietary technology.

Reliable High-Tech





1. Full servo architecture: Replaces traditional gear and shaft systems with independent servo drives for maximum precision, smoother motion, reduced maintenance, and faster setup changes.
2. Long term durability: Servos with 35% power reserve for extended lifetime and consistent performance under heavy loads.
3. Chains are obsolete; Patented lugged belts square and transport blanks cleanly, precisely, and contamination-free.
4. Local technical support and parts.

User friendly

1. With dual pressure rollers and a touch-activated pneumatic clamp, the film feeding unit makes setup fast, precise, and hassle-free.
2. Pull-out gluing unit.
3. Fully servodriven for easy handling; less maintenance, smoother operation, and complete control at the operator's fingertips.
4. WiFi-enabled for remote diagnostics; fast troubleshooting and minimal interruptions.
5. Adjust foil tension on the fly thanks to a new generation of low-maintenance electronic unwinders.

Format range



| Altura 1100 | Single lane | Double lane |
|---|--|--|
|  | <p>Blank length:</p> <p>180 * 760 mm 7.08 * 29.92 in</p> | <p>Blank length:</p> <p>180 * 760 mm 7.08 * 29.92 in</p> |
|  | <p>Blank width:</p> <p>150 * 1100 mm 5.90 * 43.30 in</p> | <p>Blank width:</p> <p>150 * 530 mm 5.90 * 20.86 in</p> |
|  | <p>Window length:</p> <p>50 * 450 mm 1.97 * 17.71 in</p> | <p>Window length:</p> <p>50 * 450 mm 1.97 * 17.71 in</p> |
|  | <p>Window width:</p> <p>50 * 920 mm 1.97 * 36.22 in</p> | <p>Window width:</p> <p>50 * 500 mm 1.97 * 19.68 in</p> |